# ROTADAIRON® SMA 305

# PNEUMATIC SEEDER FOR TRACTOR

SOIL PREPARATION

**SEEDING** 

**OVERSEEDING** 

DETHATCHING SPIKING

MULCHING





# PNEUMATIC SEEDER FOR TRACTOR

# **SMA** 305

### **Functions of the seeder SMA 305**

This seeder has been designed to seed most varieties of turf such as pastures, fescues, ryegrass, etc. on large surfaces. It is equipped with a pneumatic seeder and two cast iron rollers, allowing seeding in one pass. It is used on land previously worked with a soil preparation/stone burier.

## Quality of service





A large stock of spare parts is permanently maintained at our factory. Our partners have online tools and quick access to manufacturer information. Maintain the quality and performance of your Rotadairon® by using only original


JWING ICAI TOUCH	1	Swing	rear	roller
------------------	---	-------	------	--------

- Locking of the oscillation of the rear roller for road travel
- Drive wheel allowing the deposit of the seed in proportion to the advance
- 4 Access platform for the tank
- Front and rear roller scraper
- Pneumatic seeder

Machine	SMA 305		
Seeding width	3310 mm (130"1/4)		
Total width	3600 mm (141" <sub>3/4</sub> )		
Weight	1640 Kg (3615.5 lb)		
Tractor : Required power	60 - 100 CV		
Front roller type	Cast iron serrated disc roller		
Front roller diameter	Ø 400 mm (15" 3/4)		
Rear roller type	Cast iron serrated disc roller		
Rear roller diameter	Ø 295 mm (11" 1/2)		
3 point hitch	Categorie 2		
Tractor forward speed	3 to 8 Km/h (1.8 to 5 mph)		
Transport dimension w x L x H	3600 mm x 2420 mm x 2340 mm (141" 3/4 x 95" 1/4 x 92")		
Seeder			
Type of seed drill	Pneumatic seed drill		
Seed rate adjustement	Dosing ruler		
Seed drill capacity	750 liters (198 US gal)		
Option	Available in double rear cast iron rollers		









**ROTADAIRON** Départementale 92 - Les Hunaudières 72230 Mulsanne - France Mail: contacts@rotadairon.fr Phone number: (33) 2 43 422 422

