

ROTADAIRON®

TR 150

SOIL PREPARER / MARKET GARDENING

SOIL PREPARATION

SEEDING

OVERSEEDING

DETHATCHING
SPIKING

MULCHING

SPECIAL APPLICATIONS



MADE IN FRANCE

SOIL PREPARER / MARKET GARDENING

TR 150

Functions of the stone burier TR 150

The TERRAGRO developed by ROTADAIRON in collaboration with the professionals of the horticultural and market gardening sector is a preparator-burier for seedbeds or plantations, in beds or in forms. The TERRAGRO works the soil surface and respects its agronomic structure.

Its oversized rotor with reverse rotation throws stones, plant waste and soil against the selection grid, and, by densimetry, deposits the coarse elements which are then covered with fine soil.

The beds have, in all points, a perfect homogeneity of density which favors a more grouped germination of seeds and a faster recovery of the plants.

The TERRAGRO can thus work in all types of soil (sand, clay, silt, pebbles) while ensuring an ideal quality of preparation.





Quality of service

A large stock of spare parts is permanently maintained at our factory. Our partners have online tools and quick access to manufacturer information.

Maintain the quality and performance of your Rotadairon® by using only original parts.

- 1 Oversized rotor
- 2 Anti-pad blades (Rotadairon® patent)
- 3 Selection grid fingers
- 4 Torque limiter with dry friction and flywheel
- 5 Soil preparation principle
- 6 Working depth adjustment
- 7 Forms creation principle
- 8 Grader blade
- 9 Option : Front discs

Machine	TR 150
Working width	1500 mm (59")
Total width	1880 mm (70" 4/5)
Weight with mesh metal roller	850 Kg (1873 lb)
Tractor : Required power	45 - 70 CV
Tractor : Max track width	1.7 meters (66" 4/5)
Working depth (max)	160 mm (6" 1/4)
Rotor outer diameter	400 mm (15" 3/4)
Depth adjustment	Support on rear roller adjustable by screw jacks
Number of blades	48
Grid finger spacing	35 mm (1" 3/8)
3 point hitch	Categories 1 & 2
PTO speed	540 tr/min
Tractor forward speed	0.8 to 1,5 Km/h (0.5 to 0.9 mph)
Transmission	Angle gearbox + Oil bath chain
Security	Torque limiter with dry friction and flywheel
Transport dimension w x L x H	1900mm x 2100mm x 1200mm (74" 2/3 x 82" 2/3 x 47" 1/4)
Option	Front discs



ROTADAIRON
Départementale 92 - Les Hunaudières
72230 Mulsanne - France
Mail : contacts@rotadairon.fr
Phone number : (33) 2 43 422 422



www.rotadairon.fr