ROTADAIRON®

RD 100

STONE BURIER FOR MICRO-TRACTOR

WEEDING

RAKING

SOIL PREPARATION

SEEDING

OVERSEEDING

DETHATCHING-SPIKING

MULCHING





STONE BURIER FOR MICRO-TRACTOR

RD 100

Functions of the stone burier RD 100

This soil preparer and stone burier is designed for micro-tractors. It allows the building or renovation of green spaces by preparing the seed bed before seeding. The machine is multi-purpose, it allows tilling, burying (stones, rubbish, herbs, etc.), levelling, mixing and rolling the surface. The use is done live or on a ground previously decompacted in depth and cleared of large stones.

Quality of service


A large stock of spare parts is permanently maintained at our factory. Our partners have online tools and quick access to manufacturer information. Maintain the quality and performance of your Rotadairon® by using only original

- 1 Oversized rotor
- (2) Anti-pad blades (Rotadairon® patent)
- 3 Selection grid fingers
- Oil bath torque limiter at rotor end
- 5 Soil preparation principle
- 6 Working depth adjustment
- 7 Grader blade
- 8 Option : Rear mesh roller side adjustment device by cylinder
- (9) Option : Stainless Steel Gravity grass seeder

| Machine | RD 100 |
|-------------------------------|--|
| Working width | 1100 mm (43"1/4) |
| Total width | 1610 mm (63" _{1/2}) |
| Weight with mesh metal roller | 405 Kg (892.8 lb) |
| Tractor : Required power | 22 - 35 CV |
| Tractor : Max track width | 1,34 meters (52" _{3/4}) |
| Working depth (max) | 140 mm (5" _{1/2}) |
| Rotor outer diameter | 400 mm (15" _{3/4}) |
| Depth adjustment | Support on rear roller adjustable by screw jacks |
| Number of blades | 36 |
| Grid finger spacing | 20 mm (4/5'') |
| 3 point hitch | Categories 1 & 2 |
| PTO speed | 540 tr/min |
| Tractor forward speed | 0.8 to 1,5 Km/h (0.5 to 0.9 mph) |
| Transmission | Angle gearbox + Oil bath chain |
| Security | Oil bath torque limiter at the end of the rotor |
| Transport dimension w x L x H | 1520 mm x 1570 mm x 995 mm (59" 3/4 x 61" 3/4 x 39" 1/4) |
| Options | - Rear mesh roller side adjustment device by cylinder - Ventilated spline-slit seeder (SCV 100) - Spiral roller |













ROTADAIRON Départementale 92 - Les Hunaudières 72230 Mulsanne - France Mail: contact@rotadairon.fr

Phone number: (33) 2 43 422 422



www.rotadairon.fr